

Appln No.: 09/120,856

Page 1 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

1/10





FIG. 1

11 pages

Appln No.: 09/120,856

Page 2 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)**2/10****FIG. 2**

Appln No.: 09/120,856

Page 3 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

3/10






FIG. 3

Appln No.: 09/120,856
Applicant(s): Eric R. Fossum, et al.
SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

Page 4 of 10

4/10**FIG. 4A****FIG. 4B**

Appln No.: 09/120,858
Applicant(s): Eric R. Fossum, et al.
SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

Page 5 of 10

5/10




FIG. 5A


Appin No.: 09/120,856

Page 6 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

6/10



Appln No.: 09/120,856

Page 7 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

7/10





FIG. 6

Appln No.: 09/120,856

Page 8 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)**8/10****FIG. 7**

Appln No.: 09/120,856

Page 9 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)

9/10





FIG. 8

AppIn No.: 09/120,856

Page 10 of 10

Applicant(s): Eric R. Fossum, et al.

SINGLE SUBSTRATE CAMERA DEVICE WITH CMOS IMAGE
SENSOR (AS AMENDED)**10/10**

Array Size	256 x 256
Pixel Size	20.4 μm
Technology	1.2 μm n-well CMOS (HP)
Maximum Clock Rate	10 MHz
Minimum Clock Rate	none
Maximum Pixel Rate	2.5 MHz
Maximum Integration Delay	16 x 10 ⁹ clock periods or 1600 secs at 10 MHz

FIG. 8